

INTRODUCING A NEW

# GLOBAL POWER



**EXACT FIT BATTERIES**



AVAILABLE IN

**FLOODED & AGM TECHNOLOGIES**

*Today's automotive manufacturers are increasing their standards for replacement batteries worldwide. Batteries must not only meet specific power ratings, they have to match cover designs, dimensional configurations, case hold-down requirements and critical venting systems to comply with strict original equipment requirements.*

*The **DEKA EN\* EXACT FIT BATTERY LINE** helps take the worry out of meeting these strict standards. These batteries are especially designed to meet specialized needs while providing an exact fit for import and domestic vehicles.*

*\* (European Norm, formerly DIN Deutsche Industrie Normen)*





# EXACT FIT BATTERIES

The **DEKA EN EXACT FIT BATTERY LINE** consists of the most popular international battery sizes. It also features two advanced power Absorbed Glass Mat (AGM) batteries providing all the benefits of AGM technology in an exact fit design.

## FLOODED FEATURES

- Designed to meet power, configuration and venting requirements of strict OEM standards
- Maintenance-free delivers maximum starting power without adding water
- Compu-cast power path grids assure highest quality and optimal performance
- Deep pocket envelope separators protect plates to reduce shorts for extended life
- Over 250 quality control checks make Deka EN Batteries one of the most reliable lines in the world

## AGM FEATURES

- Meets OEM AGM requirements for exact fit replacement
- Electrolyte absorbed by micro-porous glass separators eliminates acid spills and terminal corrosion
- Tightly "packed" construction and calcium reinforced grids provide greater resistance to shock and vibration
- Provides plenty of starting power at lower temperatures
- True maintenance-free performance means longer life with hassle-free service
- Superb dual purpose design delivers excellent starting and accessory power
- Highly porous separators lowers resistance and increases power

GROUP NO.	EN SIZE	DIN SIZE	PART NO. WET	PERFORMANCE LEVEL				SUGG. WARR.	WEIGHT WET	MAXIMUM OVERALL DIMENSIONS						FOOT NOTES
				CCA @ 0°F	RES. CAP	20 A.H. RATE	REF. CA			LENGTH		WIDTH		HEIGHT		
12-VOLT EUROPEAN PASSENGER CAR - LIGHT TRUCK - VAN CALCIUM/SILVER MAINTENANCE-FREE																
40R	66LB	T6	640RMF	650	105	50	810	70	37	11	278	6 $\frac{1}{8}$	175	6 $\frac{1}{8}$	175	17,22
41	54LB		641MF	675	110	64	830	70	38	11 $\frac{1}{16}$	293	6 $\frac{1}{8}$	175	6 $\frac{1}{8}$	175	22
42	45LB		642MF	475	70	40	590	70	29	9 $\frac{1}{16}$	242	6 $\frac{1}{8}$	175	6 $\frac{1}{8}$	175	
47	55L2	H5	647MF	600	95	60	750	70	36 $\frac{1}{2}$	9 $\frac{1}{16}$	242	6 $\frac{1}{8}$	175	7 $\frac{1}{2}$	190	17,22
48	66L3	H6	9AGM48	760	120	70	875	70	45 $\frac{1}{2}$	11	278	6 $\frac{1}{8}$	175	7 $\frac{1}{2}$	190	13,17,22
48	66L3	H6	648MF	700	120	70	875	70	42	11	278	6 $\frac{1}{8}$	175	7 $\frac{1}{2}$	190	17,22
49	88L5	H8	9AGM49	900	180	95	1035	70	58 $\frac{1}{2}$	13 $\frac{3}{16}$	354	6 $\frac{1}{8}$	175	7 $\frac{1}{2}$	190	13,17,22
49	88L5	H8	649MF	900	185	100	1080	70	56 $\frac{1}{2}$	13 $\frac{3}{16}$	354	6 $\frac{1}{8}$	175	7 $\frac{1}{2}$	190	17,22
90	45LB	T5	690MF	600	90	45	745	70	33 $\frac{1}{2}$	9 $\frac{1}{16}$	242	6 $\frac{1}{8}$	175	6 $\frac{1}{8}$	175	17,22
91	66LB	T6	691MF	700	100	50	875	70	36 $\frac{1}{2}$	11	278	6 $\frac{1}{8}$	175	6 $\frac{1}{8}$	175	17,22
92	77LB	T7	692MF	650	130	75	780	70	37	12 $\frac{1}{2}$	317	6 $\frac{1}{8}$	175	6 $\frac{1}{8}$	175	17,22
93	88LB	T8	693MF	800	145	65	960	70	46 $\frac{1}{2}$	13 $\frac{3}{16}$	354	6 $\frac{1}{8}$	175	6 $\frac{1}{8}$	175	17,22
94R	77L4	H7	694RMF	765	135	80	910	70	45	12 $\frac{1}{16}$	315	6 $\frac{1}{8}$	175	7 $\frac{1}{2}$	190	17,22
95R		H9	695RMF	850	190	110	1020	70	64 $\frac{1}{2}$	15 $\frac{1}{2}$	394	6 $\frac{1}{8}$	175	7 $\frac{1}{2}$	190	17,22
97R	55L2	H5	697RMF	600	95	60	750	70	36 $\frac{1}{2}$	9 $\frac{1}{16}$	242	6 $\frac{1}{8}$	175	7 $\frac{1}{2}$	190	17,22

### FOOTNOTES:

- 13 – Absorbed glass mat technology
- 17 – Includes handle
- 22 – Flush manifold vented cover

All batteries are manufactured in black polypropylene cases and covers.  
 All batteries conform to BCI specifications.  
 All batteries are maintenance-free calcium grids.  
 CA ratings @ 32°F for comparison only.



QUALITY SYSTEM  
 CERTIFIED TO  
**ISO 9001**  
**ISO/TS 16949**  
**ISO 14001**

**"POWERED FOR PERFORMANCE"®**

DISTRIBUTED BY:

**EAST PENN manufacturing co., inc.**

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4781  
**Order Department Hotline: 610-682-4231**  
 www.dekabatteries.com • e-mail: eastpenn@eastpenn-deka.com