Mr./Mrs	s./Ms.:								Mode	l:						F	Reg. N	lo.:																									
Invoice/Job No.:						_	Odometer Reading:								V.I.N.:																		C	1	AA								
Servic	e type:	0	A	0	В		0	A	0	В	0	A	0	E	3	0	A	(	О В	(	0	А	0		В	0	)	A	0	В									VE				
Month ,000 ki	s: m:	3 6	6 12	9 18	12 24		15 30	18 36	21 42	24 48	27 54	30 60	) 33 ) 66	3	6 2	39 78	42 84	4	45 48 90 96	3 5 5 10	51 02	54 108	57 114	, 4 1	60 120	63 12	3 6 1	66 32	69 138	72 14					D	ISC	0	VEF	RY 4	4 / L	.R4	ŀ	
	/Lubricate/F	Replace		ourco	ost ind				duled 1	ime e		iten		_							L					1				1			(N	ON 3	3.0 T	DVe	6 MC	DEL	s то	11 <b>M</b> `	AR	DUC	JUS
Check	- After the	checkin	g pro	cedur	e, clea	anin	g, adjı	stin	g, repa	airing	or rep	laci	ng is sı	ubjec	t to e	extra	labou	ır a	ind mate	erial o	cost.	•												N	IAIN	<b>NTE</b>	NA	NCE	CHE	CK	SHE	ET	
	0	OIL	SER	VICI	=																									•			NNE										
1.													,000 k			الم ما	lion	<b>.</b>		33	3.												/te le										
2.		3 m	onth	s/6	,000	km	)		•				nd disl							34	4.					neci Iain	k da tena	ttery Ince	/ co <b>e ba</b>	nalti Itter	on a y fit	ana ( ted	heck MEI	VA I	i-up <b>mar</b> i	batt kets	tery <b>5 on</b>	eieci Iy	roiyt	e iev	ei - I	IOW	
3.			oect r <b>00 kn</b>		whee	el sp	beed	sen	sor ha	arne	ss for	da	mage	(Ev	very	3 m	ontl	ns.	/			Α		В	M	AIN	SE	RVI	CE	(UN	DEF	r ve	HICL	.E)									
4.		Dra	in fue	el sec	limer	ntor	(2.7	LD	iesel)	(Ev	ery 3	m	onths	/ 6,	000	km)	)			35	5.		] [							land													
5.		Adju	ust th	e ele	ctric	par	rk bra	ke	shoes	Ev	ery 3	3 m	onths	/ 6,	000	km	)	10	000	36 37			24	40k 40k	R	enev	wm wai	anu iton	ai g natio	eard trai	OX ( ISM	)    ( <b> </b> issic	<b>very</b> n oil	and	<b>yea</b> filte	rs) er (F	ver	v 10	vear	s)			
6.		km)		e cor	naitio	on o	r the e	elec	tric pa	ark d	акез	sys	tem <b>(E</b>	ver	y 3 I	non	itns/	0,	000	- 38	8.		12	20k	Re	ene	w tra	ansf	er b	OX C	il, r	epla	ce dra	ain a	and 1	fill p	lug	wash	ners	5)			
	A B	MA		RVI	CF (	VFF		= IN	ITERI	OR)										39 40				2014	Re	ene	w fro	ont a	and	rear ffere	axl	e oil	(Eve	ry 1	10 ye	ears	5)						
7.									of sea		nd sea	atb	elts							40			⊿ ך	<u>20k</u>		heck	k for	fre	e pla	av in	all	susp	ensio	on ə	ind t	boc	/ mc	ountir	ng ru	bber	S		
8.		Che	ck op	perat	ion c	of al	I lam	os, I	horns	and	warn	ning	indica							42			ΪĒ		C	hecł	< CO	ndit	ion (	of al	SU	sper	sion.	driv	/esh	nafts	and	d stee	ering	boot	s an	nd ga	aite
9.		∃ blac		perat	ion c	of fro	ont/re	ar v	vipers	sanc	was	ner	s and	con	ditic	n oi	rwip	er		43						epia hecł	ce a	all fle uall	exib v br	ie bi ake	ake ser	nos vo h	es <i>(E</i> ose, b	: <b>ver</b> orak	<b>у 6</b> 	yea Jel	rs) PAS	and	clut	ch pi	oes.	uni	ons
10.		Sele	ect th						nd dr	ive tl	ne ve	hic	le 3 to	4 v	ehic	le le	ngth	s tl	hen	44					ar	nd e	lecti	rical	hai	nes	ses	for c	hafin	g, le	eaks	and	d co	rrosi	on	o p.	,		
11.			elect				gear	S												45 46						heck	(for	flui hau	d le	aks	n fc	n los	ıks, s		rity	and	dan	ane					
				•				= F.	XTER	IOR										47			16		C	hecł	< ste	erir	ng ro	d ba	all jo	int fi	xings	s and	d cor	nditi	ion d	of bal	l join	ts an	d du	ist c	ove
10												anı	nual c	orro	sion	ins	pecti	on	1	48	8.					hecł ama		ock	abs	orbe	rs/h	eigh	t sen	sors	and	1 hai	rnes	s ass	semb	oly fo	leal	kage	) ar
12.		_ she	et						•		0									49	0				lf	fault	ť lan	np(s	s) ar	e illu	mir	ated	l, inte	erroç	gate	tha	t sys	stem	usin	g IDS	S\SD	)D a	nd
13.			еск ту	re pr	essu	Ires	, con		n and	trea	aa ae 7	ptn								50						port				ot (e	~~~	1.1.1	RNIN	6.0	VOR	220				-			
14.			nove							L										5			$\left  \right $			eset	ser	vice	e int	si <b>(s</b> erva	l an	noui	cem	ent	indic	cato	e) r						
15. 16.		_ Rep ∃ Rep	lace	brak Jel fil	e flui ter e	id <b>(1</b>	Every	2 y 2 7	/ears L Die	)° sel)										52			ĮĒ							reco			N										
17.		Refi	it roa	d wh	eels	to c	ppos	ite	sides	of th			axle (							53 54			╎┝			eset hecł	i oii K for	anv	i inc v ap	dicat	or ( able	outs	ed) standi	ina :	serv	ice	actio	ons c	r rec	alls			
													vith un struct							55			jÈ										of vel								work	k rec	uir
18.			nage	51100	V IIIC	100	0101/1	aun		1 07	Cina	100	511401	10113		iiai	i biat	100	5101																								
19.	120	Ren									ootol	h٥	fuel fl	<u></u>	and	lubri	iooto	de	oor																								
20.		che		Jerai		n ut		IECI	15, 00		Calci	Πα	IUEI II	ap a	anu	lubi	icale	uc	501																								
21. 22.		] App ] Che	ly lub ck co	oricai onditi	nt to on o	doo f re	or sea mova	ls - ble	Russ towb	s <i>ian</i> ar	and l	Noi	rdic m	ark	ets	only	/																										
									NNET	)																																	
23. 24.							ecific y 10													тι	ho m	agint	0021	nco	ito	me	licto	d a	ro th		roc		ende	d fo	r vol	hicle		orati	na 11	ndor	ardu		
25.	72	Ren	iew s	park	plùg	s	-		,											dr	rivin	g, ro	ad a	and	l cli	imati	ic co	ondi	tion	s. Me	ore	requ	ent a	tten	tion	may	/be	nece	ssary	/ if th	e ve	hicle	e is
26. 27.			iew a	ir cle	aner	ele	ement	( <b>P</b>	etrol) 7L D	ioso	0																						eratu				ndit	ions,	off r	oad o	lrivir	ng o	·
27. 28.		Che	ck co	onditi	on o	f an	ncillar	y dr	iving	belts																							on ba tion c				ted a	and se	ervice	port	olio I	book	
29.	120	Ren	iew a	ncilla	arv d	rivir	na be	Íts (	Ever	v 5 v	ears	)			ماند			!			ndor					- 1																	
30.	96	Ren (2.7	iew fi <b>'L Di</b> e	ont a esel	and r Ever	ear ′v 4	cam: year	snai s)	it timi	ng b	eits, t	ens	sioners	s an	a te	nsio	mert	201	ι										<u>.</u>										-				
31. 32.		🗋 Ċhe	ck/tc	p-up	brak	ke, F	PASa	and					and sc using							Na	ame	:							Sig	natu	re: .								. Dat	:e:		•••	•••

WARNING: Two wheel roller tests must not be carried out. Four wheel roller tests must be limited to 5 km/hour (3 miles/hour).

## **IMPORTANT - OIL CHANGE DIESEL ENGINES**

If the vehicle is operated on fuel with a high sulphur content (over 0.7%) the oil change intervals must not exceed 6,000Km (3750 miles) If the vehicle is operated on fuel with a moderate sulphur content (between 0.3 - 0.7%) the oil change intervals must not exceed 12,000Km (7500 miles)

## IT IS RECOMMENDED THAT:

At 144,000 Km (90,000 miles) or every six years, whichever is the sooner, all hydraulic brake fluid hoses should be renewed

After 80 Km (50 miles) continuous use in severe off road conditions - wading, deep mud and abrasive grit/slurry - the electric park brake should be inspected, cleaned and adjusted, and the ancillary drive belt should be inspected and cleaned.

Air suspension vehicles used extensively in arduous/ off road conditions will require the compressor inlet filter to be replaced at more regular intervals.

When the vehicle is used in dusty or field conditions or deep wading, frequent attention to the air cleaner may be required.

When the vehicle is used in areas where fuel quality is poor, more frequent draining of the fuel filter/ sedimentor may be required.

For full details regarding the operations contained in this maintenance check sheet, please refer to the workshop manual.

## GLOSSARY:

OIL SERVICE = The oil service is applicable to all vehicles. It is carried out at 3 month or 6,000 Km intervals, whichever occurs first.

MAIN SERVICE = The main service is applicable to all vehicles. It is carried out at 6 month or 12,000 Km intervals, whichever occurs first.

Main Service "A" is applicable at 6 months/12,000 Km, 18 months/36,000 Km, 30 months/60,000 Km, 42 months/84,000 Km and so on.

Main Service "B" is applicable at 12 months/24,000 Km, 24 months/48,000 Km, 36 months/72,000 Km, 48 months/96,000 Km and so on. Some items do not need to be carried out at every main service and these items are identified by an indicator in the tick box e.g. 60k (This indicates that this item is only applicable every 60,000 Km)

NOTE: The service required should be at the time or distance stated, which ever occurs first.

## **Comments/Remedial Work**